

**ELECTRIC PUMP AND HAND PUMPS 油壓式泵浦**



ITEM NO.	Max. Press output	Pump speed	Pressure rating (kgf/cm <sup>2</sup> )	Oil Delivery (l/m <sup>3</sup> )	Reservoir Capacity	Weight (kgs)	Dimensions LxWxH(mm)	Remarks
CTE-25AS	10,000 P.S.I	TWO speed	Low 0-20 High 20-700	2.2 0.32	4000c.c	15.5	250x180x320	Pressure holding pump
CFP-800-1	10,000 P.S.I	TWO speed	1st 350 2nd 10,000	2.3 13	400c.c	14	250x140x250	Foot
CP-700	10,000 P.S.I	TWO speed	1st 350 2nd 10,000	2.3 13	900c.c	10	510x140x150	Hand

**HYDRAULIC COMPRESSION HEADS (700kgf/cm<sup>2</sup>) 油壓式壓著工具**



ITEM NO.	Output (tons)	Weight (kgs)	Head (kgs)	Applicable Range			Standard Dies	Shape
				JIS	AWG	DIN		
CO-325A	17	6	4	325	650	400	MALE 16-70,90-150,185-400 FEMALE 16-25,35,50-70,95,120,150,185-240,300,400	Point
CO-325B	17	8	4	325	650	400	FEMALE 16-25,35,50-70,95,120,150,185-240,300,400X9Set	Hexagon
CO-500B	20	11	7	400	1000	500	70,95,120,150,185-240,300,400,500X9Set	Hexagon
CO-630A	35	20	16	500	1200	630	With 630 die only 50-70,95,120,150,185-240,300,400,500,upon request	Hexagon
CO-630B	30	19	9	500	1200	630	With 630 die only 50-70,95,120,150,185-240,300,400,500,upon request	Hexagon