


NON-INSULATED FLANGE SPADE TERMINALS

TERMINAL MATERIAL : COPPER



WIRE RANGE mm ²	ITEM NO.	STUD SIZE		DIMENSION inch mm					AWG	MAXIMUM ELECTRIC CURRENT
	BRAZED SEAM	d2φ		B	L	E	Dφ	dφ		
0.5-1.5 mm ²	1.25-3YSAL	#4	3.2	5.7	16.0	4.5	3.4	1.7	22-16	19
	1.25-3YSL	#6	3.7	5.7	16.0	4.5	3.4	1.7		
	1.25-3YWL	#6	3.7	6.2	16.0	4.5	3.4	1.7		
	1.25-4YSL	#8	4.3	6.4	16.0	4.5	3.4	1.7		
	1.25-4YWL	#8	4.3	7.2	16.0	4.5	3.4	1.7		
	1.25-5YL	#10	5.3	8.0	16.0	4.5	3.4	1.7		
	1.25-6YL	#1/4	6.4	10.7	17.0	4.5	3.4	1.7		
1.5-2.5 mm ²	2-3YSAL	#4	3.2	5.7	16.0	4.5	4.0	2.3	16-14	27
	2-3YSL	#6	3.7	5.7	16.0	4.5	4.0	2.3		
	2-3YWL	#6	3.7	6.2	16.0	4.5	4.0	2.3		
	2-4YSL	#8	4.3	6.4	16.0	4.5	4.0	2.3		
	2-4YWL	#8	4.3	7.2	16.0	4.5	4.0	2.3		
	2-5YL	#10	5.3	8.0	16.0	4.5	4.0	2.3		
	2-6YL	#1/4	6.4	10.7	19.0	4.5	4.0	2.3		
4-6 mm ²	3.5-4YSL	#8	4.3	8.0	18.0	6.3	5.0	3.0	12-10	48
	3.5-5YSL	#10	5.3	8.0	18.0	6.3	5.0	3.0		
	5.5-3YL	#6	3.7	8.2	19.5	6.5	5.6	3.5		
	5.5-4YL	#8	4.3	8.2	19.5	6.5	5.6	3.5		
	5.5-5YL	#10	5.3	9.0	19.5	6.5	5.6	3.5		
	5.5-6YL	#1/4	6.4	12.0	24.0	6.5	5.6	3.5		
8mm ²	8-6YL	#1/4	6.4	12.0	24.0	8.6	6.9	4.5	8	62