







## TIMER 限時繼電器

CLASSIFICATION 類別		TIMER 限時繼電器			MULTI RANGE TIMER 多段式限時繼電器			DIGITAL TIMER 數字式限時繼電器			MULTI RANGE TIMER 多段式限時繼電器	
ITEM NO. 型號		TH3A-N□			TH3M-N□			TH3D-N□			TM48S	
APPEARANCE 外觀												
DIMENSIONS(mm) 尺寸		50Hx40Wx57.5D			50Hx40Wx57.5D			60Hx48Wx79D			48Hx48Wx78D	
MOUNTING & SOCKET 安裝與 器具座	SURFACE(-N) 露出型	PF085A			PF085A			8PFA			P2CF-08	
	FLUSH(-Y) 埋入型										Y48 & P3G-08 or Y48 & Us08	
FULL TIMING RANGE 時間範圍		SEC: 1,3,6,12,30,60,180 MIN: 3,6,12,30,60,180 HR: 3,6,12,24			A: 1S,10S,1M,10M B: 3S,30S,3M,30M C: 6S,60S,6M,60M O: 1M,10M,1H,10H E: 3M,30M,3H,30H			SEC: 9,99,99,9,999 MIN: 99,9,999 HR: 99,9,999			1.1S,10S,1M,10M 2.3S,30S,3M,30M 3.6S,60S,6M,60M 4.3M,30M,3H,30H	
RATED VOLTAGE 額定電壓		DC(V): 12,24 AC(V): 12,24,110,220,240,50/60Hz									24V~240V AC/DC	
O/P 輸出 CONTACT	MODEL 型式	TH3A-NA	TH3A-NB	TH3A-NC	TH3M-NA	TH3M-NB	TH3D-NA	TH3D-NB	TH3D-NC	A	B	
	TIME LIMIT 限時1C	5A		5A	5A		5A		5A	5A		
	TIME LIMIT 限時2C		5A			5A		5A			5A	
	INSTANTANEOUS 瞬時1C	5A			5A		5A			5A		
LIFE 壽命	MECHANICAL 機械	5X10 <sup>6</sup> times							10 <sup>6</sup> times			
	ELECTRICAL 電氣	10 <sup>5</sup> times							10 <sup>5</sup> times			
ACCURACY 精確度	REPEAT ERROR 重複誤差	±1%max			±0.05 sec			±1%max				
	SETTING ERROR 設定誤差	±10%max			0			±10%max				
	VOLTAGE ERROR 電壓誤差	±1%max			±0.05 sec			±1%max				
	TEMP. ERROR 溫度誤差	±2%max			±0.05 sec			±2%max				
RESET TIME 復歸時間		0.1 secretary max			0.3 sec max			0.1 sec max				
CONSUMED POWER 消耗功率		2VA			3VA			2VA				
AMBIENT TEMPERATURE 使用周圍溫度		-10°C~+55°C			-10°C~+55°C			-10°C~+55°C				
AMBIENT HUMIDITY 使用周圍濕度		45~85% RH			45~85% RH			45~85% RH				
WEIGHT 重量		160g			230g			180g				